



Feature:

- * Low power consumption
- * PCAP multi-touch with 10 fingers
- * True flat surface design
- * 7*24 non-stop working
- * Android 4.4.4
- * Standard VESA design 75*75/100*100
- * Offer OEM / ODM customized design

Datasheet

Model		TSAIO-2360-PCT	
Mainboard	CPU	Rockchip Quadcore RK3188	
	Frequency	1.5GHz	
	Graphic	Mali-T76x / PowerVR, support 4K*2K	
	Display ports	LVDS/ HDMI	
	Fan / Fanless	Fanless	
Memory		1G	
Flash		8G (Default)	
Display method		Horizontal / Vertical	
Speaker		Built-in 3W+3W	
Video Format		Support 1920*1080 HD, H.265, VP8, RV, WMV, AVS, H.264, MPEG4	
Audio Format		Support MKV, AVI, RM, RMVB, MP4, MOV, VOB, DAT, FLV, 3GP..etc	
Output Ports	External Port	USB	2
		RJ45	1
		Headphone Jack	1
		SD Card Slot	1
		DC 12V	1
		Mini USB	1
	Network	Realtek 8111E 10/100/1000M	
Environment	Working Temp	-10°C~60°C	
	Working Humidity	10%~95%~@40°C	
	Storage Temp	-20°C~70°C	
Installation Method		Wall-mounted / Desktop / Floor standing	
O.S		Android 4.4.4	

Display Screen

Screen Size	23.6"
Resolution	Full HD 1920*1080, Support 4K*2K
Brightness	300nits
Contrast Ratio	1000/1
Response time	6ms
Touch screen	PCAP Multi-touch (G+G)

Optional Hardware

Size available	10.1"/ 11.6"/ 13.3"/ 15.6"/ 18.5"/ 21.5"/ 23.6"/ 27"/ 32"
Camera	Support 5M AF Camera(Optional)
Touch screen	Can be with touch screen / Without touch screen
Bluetooth	Support Bluetooth 4.0
3G/4G Module	Support most of brand 3G/4G module
IR Remote control	Support

Packing Info

Outline Dimension	763.77*457.21*47mm
Carton Dimension	860*580*148mm
G.W	10.8kg

