

ORION PCAP professional display

- Wide dynamic range of Interactive 32" ~ 86"



Features

Design

- ✓ Edge to edge glass (Bezel free)
- ✓ Robust metal works
- ✓ All rounded 4 corners
- ✓ VESA wall & Side mountable

Display

- ✓ Long term usable commercial LCD panel (24/7/365)
- ✓ Ultra HD resolution
- ✓ Compatible panel for
 - Landscape, Portrait, Table

Functionality

- ✓ Fastest P-CAP touch (10p/50p)
- ✓ Alternative interface
 - HDMI, DP, DVI, VGA
- ✓ Ventilation FAN

Option

- ✓ PC / Android built in
- ✓ Various glass coating (AR, AG, AF, Mirror etc)
- ✓ Screen rotation button



Specification

Model	OLSK-3250CP	OLSK-4350CP	OLSK-4650CP	OLSK-5550CP	OLSK-6550CP	OLSK-8650CP
Panel Size (inch)	32	43	46	55	65	86
Aspect Ratio	16:9	16:9	16:9	16:9	16:9	16:9
Max. Resolution	FHD	UHD	FHD	UHD	UHD	UHD
Contrast Ratio (Typ.)	1300:1	1000:1	4000:1	1100:1	1100:1	1200:1
Brightness (panel) cd/m ²	450	400	500	500	500	500
Viewing Angle (H)/(V) (Typ.)	178°/178°	178°/178°	178°/178°	178°/178°	178°/178°	178°/178°
Input Signal	HDMI, DVI-D, VGA	HDMI 2.0 x 2 DP 1.2 x 2	HDMI, DVI-D, VGA	HDMI 2.0 x 2 DP 1.2 x 2	HDMI 2.0 x 2 DP 1.2 x 2	HDMI 2.0 x 2 DP 1.2 x 2
Audio	Input/output	HDMI Φ3.5 Phone Jack Speaker	HDMI DP	HDMI Φ3.5 Phone Jack Speaker	HDMI, DP Φ3.5 Phone Jack Speaker	HDMI, DP Φ3.5 Phone Jack Speaker
	Speaker Output	10Wrms + 10Wrms (±10%)	10Wrms + 10Wrms (±10%)	10Wrms + 10Wrms (±10%)	10Wrms + 10Wrms (±10%)	10Wrms + 10Wrms (±10%)
Plug & Play	VESA DDC2B		VESA DDC2B	VESA DDC2B		
Power Input	AC 100V~240V (50/60Hz)	AC 100V~240V (50/60Hz)	AC 100V~240V (50/60Hz)	AC 100V~240V (50/60Hz)	AC 100V~240V (50/60Hz)	AC 100V~240V (50/60Hz)
Touch Technology	PCAP	PCAP	PCAP	PCAP	PCAP	PCAP
Touch Input Method	Finger, Pen (Capacitive)	Finger, Pen (Capacitive)	Finger, Pen (Capacitive)	Finger, Pen (Capacitive)	Finger, Pen (Capacitive)	Finger, Pen (Capacitive)

■ The specification is subject to change without prior notice

www.oriondisplay.net

